



6 TON MDM-ECS A105B A53B
Pipe Insert Size – 3 inch
 Sch. 40 Wt. = 7.576 lb./ft | Sch. 80 Wt. = 10.25 lb./ft

MYERS DESIGN & MFG
 8235 Lockheed Ave. Houston, TX 77061
 P: 832-581-2742 | F: 832-581-2743
 info@myersdnm.com • www.myersdnm.net



Spreader Span (ft - in)	Capacity at 45° Sling Angle (Tons)		Capacity at 60° Sling Angle (Tons)		Weight. Incl. shackles & Pipe (lbs.)		Length of Insert (ft - in)
	SCH 40	SCH 80	SCH 40	SCH 80	SCH 40	SCH 80	
2' – 4" *	6	6	6	6	76	81	16"
4'	6	6	6	6	91	102	36"
6'	6	6	6	6	106	122	60"
8'	6	6	6	6	121	143	84"
10'	6	6	6	6	136	163	108"
12'	6	6	6	6	152	184	132"
14'	6	6	6	6	167	204	156"
16'	5	6	6	6	182	225	180"

Note - Shaded Area indicates structural limit.

Offset = 6.25 inches
 Span Adder per End Cap System = 12.5 inches
 Insert Length = Span – 12.5 inches
 * - Denotes Minimum Span

MEETS OR EXCEEDS
 ASME BTH-1 & ASME B30.20
 WELDS PER AWS D14.1

Wt. per End Cap – 30 lbs.
 Top Shackles 3/4" - 4.75t
 Bottom Shackles 5/8" - 3.25t